



# Technical Data Sheet

S002a/070109B

PRODUCT NAME

**SAK-ZS-P**

TYPE

**Zinc Stearate**

## TYPICAL SPECIFICATION

- Appearance : White Powder
- Zinc Content : 10.4 – 11.4%
- FFA Content : 0.5% Max
- Moisture Content : 0.5% Max
- Softening Point : 118 - 125°C

## GENERAL INFORMATION

- Product Packaging : 25kg net paper sacks
- Storage and Handling : Full information on the handling of this product is available upon request

## PRODUCT APPLICATION

- SAK-ZS-P is our standard Zinc Stearate grade which is produced via direct reaction process that offers excellent purity.
- SAK-ZS-P is mainly used in PVC compounds. It gives good initial colour hold to the compound and acts as releasing agents and processing aids in the calendaring, injection or blow moulding process.
- It is used in the colour masterbatch production to improve pigments dispersion and enhance blending.
- It can be used as anti-tackifier in rubber industry to prevent rubber slabs from sticking together.

The above information is provided based on our best knowledge and subjected to change without prior notice. As the circumstances and conditions under which our products would be used are beyond our control, we accept no liability for any loss and damage arising from the use of such information.

**Sun Ace**

Sun Ace Kakoh (Pte) Ltd 34 Tanjong Penjuru, Jurong Town, Singapore 609030 • Tel: (65) 6264 0255 • Fax: (65) 6265 7038 • Email: saksg@sunace.com.sg • Website: www.sunace.com.sg