



Technical Data Sheet

S007a/040509/B

PRODUCT NAME

SAK-MS-P

TYPE

Magnesium Stearate

TYPICAL SPECIFICATION

- Appearance : White Powder
- Magnesium Content : 4.0 – 5.0%
- FFA Content : 1.5% Max
- Moisture Content : 5.5% Max
- Softening Point : 130 - 150°C

GENERAL INFORMATION

- Product Packaging : 20kg net paper sacks
- Storage and Handling : Full information on the handling of this product is available upon request

PRODUCT APPLICATION

- SAK-MS-P is our standard Magnesium Stearate grade which is produced via direct reaction process that offers excellent purity.
- SAK-MS-P is commonly used as a lubricant and releasing agent for the processing of thermoplastics. It is used as a dusting agent to prevent surface adhesion in the ABS plastics with minimal discolouration.
- It functions as an efficient colour dispersant in the colour masterbatch production.

The above information is provided based on our best knowledge and subjected to change without prior notice. As the circumstances and conditions under which our products would be used are beyond our control, we accept no liability for any loss and damage arising from the use of such information.

Sun Ace

Sun Ace Kakoh (Pte) Ltd 34 Tanjong Penjuru, Jurong Town, Singapore 609030 • Tel: (65) 6264 0255 • Fax: (65) 6265 7038 • Email: saksg@sunace.com.sg • Website: www.sunace.com.sg