SUNACE

Technical Data Sheet

PRODUCT NAME

SAK-LiS-PE

TYPE

Lithium Stearate

TYPICAL SPECIFICATION

- Appearance : Off White powder
- FFA Content : 2.0 % Max
- Moisture Content : 2.0 % Max
- Softening Point : 200°C Min
- Alkalinity Content : 0.1% Max

GENERAL INFORMATION

- Product Packaging : 25kg net paper sacks
- Storage and Handling : Full information on the handling of this product is available upon request

PRODUCT APPLICATION

- SAK-LiS-PE is a high melting point lubricant which can be used for production and processing of polyolefins and ABS.
- It is used in metal working as lubricant and as a hardening agent for mineral oils. It is a common component in the production of various greases.

REF. NO. : S017a/B

ISSUE DATE : 16/12/2014

REV. NO. : 0

REV. DATE : -

The above information is provided based on our best knowledge and subjected to change without prior notice. As the circumstances and conditions under which our products would be used are beyond our control, we accept no liability for any loss and damage arising from the use of such information.

Sun Ace

Sun Ace Kakoh (Pte) Ltd 34 Tanjong Penjuru, Jurong Town, Singapore 609030 • Tel: (65) 6264 0255 • Fax: (65) 6265 7038 • Email: saksg@sunace.com.sg • Website: www.sunace.com.sg