



Technical Data Sheet

PRODUCT NAME

SAK-CZ963-NP

TYPE

Non-toxic calcium-zinc One-pack Stabiliser/Lubricant

TYPICAL SPECIFICATION

- Appearance : Powder
- Moisture Content : 2.0% max

GENERAL INFORMATION

- Product Packaging : 25kg net paper sacks
- Storage and Handling : Full information on the handling of this product is available upon request

PRODUCT APPLICATION

- SAK-CZ963-NP is a non-toxic one-pack stabiliser/lubricant system designed for extrusion process. It is suitable for use in pressure and non-pressure uPVC pipe.
- It provides excellent initial colour and good colour stability and heat stability. Under proper process parameters, CZ963 would exhibit improve plate out performance.
- Dosage : 2.5 – 4.0phr is recommended depending on the formulation and machine operating conditions. Mixing temperature between 110°C -130°C is recommended

REF. NO. : M255/A

ISSUED DATE : 18/08/2011

REV.NO. : 02

REV.DATE : 06/03/2012

The above information is provided based on our best knowledge and subjected to change without prior notice. As the circumstances and conditions under which our products would be used are beyond our control, we accept no liability for any loss and damage arising from the use of such information.

Sun Ace

Sun Ace Kakoh (Pte) Ltd 34 Tanjong Penjuru, Jurong Town, Singapore 609030 • Tel: (65) 6264 0255 • Fax: (65) 6265 7038 • Email: saksg@sunace.com.sg • Website: www.sunace.com.sg