



# Technical Data Sheet

PRODUCT NAME

**SAK-ZS-PLB**

TYPE

**Zinc Stearate**

## TYPICAL SPECIFICATION

- Appearance : White Powder
- Zinc Content : 10.4 – 11.4%
- FFA Content : 0.5% Max
- Moisture Content : 0.5% Max
- Softening Point : 118 - 125°C
- On 325 Mesh : 0.5% Max

## GENERAL INFORMATION

- Product Packaging : 20kg net paper sacks
- Storage and Handling : Full information on the handling of this product is available upon request

## PRODUCT APPLICATION

- SAK-ZS-PLB is produced via direct reaction process that offers excellent purity.
- SAK-ZS-PLB is specially developed for wood lacquer industry. It functions as a sealer by closing the pores of the wood and facilitates the sanding process.

REF. NO. : S002em/B

ISSUE DATE : 26/02/2016

REV. NO. : 0

REV. DATE : -

The above information is provided based on our best knowledge and subjected to change without prior notice. As the circumstances and conditions under which our products would be used are beyond our control, we accept no liability for any loss and damage arising from the use of such information.

## Sun Ace

Sun Ace Kakoh (Pte) Ltd 34 Tanjong Penjuru, Jurong Town, Singapore 609030 • Tel: (65) 6264 0255 • Fax: (65) 6265 7038 • Email: saksg@sunace.com.sg • Website: www.sunace.com.sg